SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES:

Contain spill. Remove with inert absorbent material. Wash spill area with water.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE:

Store containers upright with lids (caps) tightly closed. Store between 40F(4C) - 100F(37.7C) Keep from freezing.

OTHER PRECAUTIONS: Keep out of the reach of children. Do not get in eyes or on skin.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:	CAS NO:	OSHA PEL-TWA:	OSHA PEL STEL:	ACGIH TLV-TWA:
Mineral Spirits Aliphatics	64742-48-9	100 ppm	200 ppm	500 ppm
Aluminum oxide	1344-28-1	15 mg/m3		10mg/m3
Petroleum hydrocarbon solvent	64742-47-8	500 ppm		100 ppm
Octamethylcyclotetrasiloxane	556-67-2	10 ppm		10 ppm

ENGINEERING CONTROLS:

VENTILATION : **LOCAL EXHAUST:** Adequate **MECHANICAL:** **OTHER:**

RESPIRATORY PROTECTION: Avoid exposure levels. When exceeded, use self contained breathing apparatus.

EYE PROTECTION: Approved Safety Glasses **SKIN PROTECTION:** Rubber or Neoprene Gloves

PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash fountain in work area is recommended.

WORK HYGIENIC PRACTICES: Observe good housekeeping practices.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Blue **ODOR:** Vanilla **PHYSICAL STATE:** Viscous Cream

BOILING POINT: 220 F 104 C **pH AS SUPPLIED:** NA

MELTING POINT: F C **SOLUBILITY IN WATER:** 90%

FREEZING POINT: F C **EVAPORATION RATE:** **BASIS (Butyl Acetate=1):** 1

SPECIFIC GRAVITY (H2O = 1): >1 **VAPOR PRESSURE (mmHg):**

VAPOR DENSITY (AIR = 1): >1

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable **CONDITIONS TO AVOID:** Open flame

INCOMPATIBILITY (MATERIAL TO AVOID): Strong acids or bases, oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

Carbon monoxide and other inidentified organic compounds may be released during combustion.

HAZARDOUS POLYMERIZATION: Will not occur **CONDITIONS TO AVOID (POLYMERIZATION):** NA

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:	CAS NO:	LD50
Mineral Spirits Aliphatics	64742-48-9	1500 mg/kg
Aluminum oxide	1344-28-1	Not available
Petroleum hydrocarbon solvent	64742-47-8	1500 mg/kg
Octamethylcyclotetrasiloxane	556-67-2	5000 mg/kg