SAFETY DATA SHEET Super APC (VOC Compliant)

SDS No: 4015-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013) Date of last Revision: 08/19/2014

1.Identification of the substance or mixture and of the supplier

- 1.1 Product identifier used on the label: Super APC
- **1.2 Other means of identification:** Not Applicable
- **1.3 Recommended use of the chemical and restrictions on use:** An automotive interior and exterior all-purpose cleaner/degreaser. This material should not be used for any other purpose than that recommended without expert advice.
- **1.4** Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party: J.B.Chemical Co., Inc.

14803 S. Spring Street Gardena, CA 90248, USA 310-532-3021 800-522-2468

1.5 Emergency phone numbers: J.B.Chemical Co., Inc.: (310) 532-3021, (800) 522-2468 Monday - Friday, 7:00am - 3:00pm PST Chemtrec: (800) 424-9300 - Outside the continental U.S.: (703) 527-3887 24 Hours

2.Hazard(s) identification

2.1 Classification of the chemical in accordance with 29 CFR 1910.1200(d) and GHS Rev.5th e.2013: This product is classified as hazardous.

Eye Damage Category 1 Skin Corrosion Category 1 Aquatic Acute Category 3


2.2 Signal word, hazard statement(s), symbol(s) and precautionary statement(s) in accordance with 29 CFR 1910.1200(f) and GHS Rev.5th e.2013:

Signal word: Danger

Hazard statement(s):

- Physical Hazards: Not Applicable
- Health Hazards: H314: Causes severe skin burns and eye damage.
- Environmental Hazard: H402: Harmful to aquatic life.

Symbol(s):



Precautionary statement(s):

SAFETY DATA SHEET Super APC (VOC Compliant)

SDS No: 4015-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013) Date of last Revision: 08/19/2014

Prevention:

P102: Keep out of reach of children.

P264: Wash hands thoroughly after handling.

P260: Do not breathe dust/fume/gas/mist/vapors/spray.

P280: Wear protective gloves/eye protection.

P273: Avoid release to the environment.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P310: Immediately call a POISON CENTER or doctor/physician.

P363: Wash contaminated clothing before reuse.

Storage: P405: Store locked up.

Disposal: P501: Dispose of contents/container in accordance with CERCLA/CWA (Section 311)/SARA Title III Regulations.

- 2.3 Describe any hazards not otherwise classified that have been identified during the classification process It may cause respiratory tract irritation.
- 2.4 Where an ingredient with unknown acute toxicity is used in a mixture at a concentration ≥ 1% and the mixture is not classified based on testing of the mixture as a whole, a statement that X% of the mixture consists of ingredient(s) of unknown acute toxicity is required: Not Applicable

3.Composition/ information on ingredients

Chemical name	CAS No.	EC No.	Concentration (Wt%)	Classification 29 CFR 1910.1200(d)/GHS
Ethylene glycol	111-76-2	203-905-0	≤ 8.00	Flam. Liq.4 H227
monobutyl ether				Acute Tox.4 H302
				Acute Tox.4 H312
				Skin Irrit.2 H315
				Eye Irrit.2 H319
				Acute Tox.4 H332
				Asp Tox.1 H304
Sodium Metasilicate	10213-79-3	Not listed	≤ 2.00	Acute Tox.4 H302
Pentahydrate				Eye Dam.1 H318
				Skin Corr.1B H314
				STOT SE3 H335
Sodium Hydroxide	1310-73-2	215-185-5	≤ 2.75	Acute Tox.3 H301
				Acute Tox.4 H312
				Eye Dam.1 H318
				Skin Corr.1A H314
				Aquatic Acute 3 H402
Ethoxylated Alcohols	66455-15-0	Not listed/	≤ 4.00	Skin Irrit.2 H315
Mixture	68551-12-2	500-221-7		Eye Irrit.2 H319

SAFETY DATA SHEET Super APC (VOC Compliant)

SDS No: 4015-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013) Date of last Revision: 08/19/2014

68002-97-1	STOT SE3 H335 Asp Tox.1 H304 Aquatic Acute 2 H401
------------	---

4.First-aid measures

4.1 Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion.

- Inhalation: If respiratory symptoms develop, move victim away from source of exposure and into fresh air. If symptoms persist, get medical attention.
- Skin contact: Clean affected areas with mild soap and water. Remove contaminated clothing, including shoes, and launder before reuse or discard. If any irritation persists, seek medical attention.
- Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. If any irritation persists, get medical attention.
- **Ingestion:** Do not induce vomiting or give anything by mouth. If victim is drowsy or unconscious, place on the left side with head down. If possible, do not leave victim unattended.
- **4.2** Most important symptoms/effects, acute and delayed: Serious eye and skin burns/irritation.
- **4.3** Indication of immediate medical attention and special treatment needed, if necessary: Persistent eye or skin irritation.

5.Fire-fighting measures

- **5.1** Suitable (and unsuitable) extinguishing media: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not discharge extinguishing waters into the aquatic environment.
- 5.2 Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products): Not Applicable
- **5.3** Special protective equipment and precautions for fire-fighters: Wear full protective clothing and self-contained breathing apparatus.

6.Accidental release measures

6.1 Personal precautions, protective equipment, and emergency procedures:

Avoid contact with spilled or released material. Immediately remove all contaminated clothing. Wear protective equipment to prevent skin and eye contact and breathing in vapors. Remove all possible sources of ignition in the surrounding area. Shut off leaks, if possible without personal risks. Use appropriate containment (of product and fire-fighting water) to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapor or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

6.2 Methods and materials for containment and cleaning up:

For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery

SAFETY DATA SHEET Super APC (VOC Compliant)

SDS No: 4015-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013) Date of last Revision: 08/19/2014

or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity (refer to Chapter 15) to the National Response Centre at (800) 424-8802.

7.Handeling and storage

7.1 Precautions for safe handling:

Avoid breathing mists or vapors. Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Use only with adequate ventilation. Wash thoroughly after handling. Do not wear contaminated clothing or shoes. Handle an open container with care in a well-ventilated area. Ventilate work place in such a way that the Occupational Exposure Limit (OEL) is not exceeded. Do not empty into drains.

7.2 Conditions for safe storage, including any incompatibilities:

For small containers, keep out of reach of children. Keep tightly closed and store in a cool and well ventilated area. Store only in approved containers and protect from physical damage. Storage should meet OSHA standards. Empty drums should be completely drained, properly bunged, and promptly shipped to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulation. Do not overheat; product will start boiling if heated above 200°F.

8. Exposure controls/ personal protection

8.1 OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available: Component(s):

Chemical name	Туре	Exposure Limit values	Source
Sodium Metasilicate Pentahydrate CAS No:10213-79-3	TWA (dust,8 hr)	2 mg/m3	Manufacturer's recommendation
Ethylene glycol monobutyl ether CAS No: 111-76-2	TWA (vapor,8 hr)	20 ppm	US. ACGIH Threshold Limit Values (01 2010)
Sodium Hydroxide CAS No: 1310-73-2	TWA (vapor,8 hr)	2 mg/m3	US. ACGIH Threshold Limit Values (01 2010)

- **8.2** Appropriate engineering controls: Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.
- 8.3 Individual protection measures, such as personal protective equipment:
 - Eye/face protection: Select and use eye/face protection to prevent contact based on the results of an

SAFETY DATA SHEET Super APC (VOC Compliant)

SDS No: 4015-1 Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013) Date of last Revision: 08/19/2014

exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

- Skin/hand protection: Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Gloves made from the following material(s) are recommended: Nitrile rubber
- Respiratory protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use and maintenance must be in accordance with regulatory requirements. If applicable, types of respirators to be considered for this material include: half-face air-purifying filter respirator suitable for organic vapors and particulates (P95).

9. Physical and chemical properties

Appearance (physical state, color, etc.):	Liquid, yellow
Odor:	Fragrant odor
Odor threshold:	Not Determined
pH:	13.0
Melting point/freezing point:	Not Applicable
Initial boiling point and boiling range:	>200 °F
Flash point:	Not Applicable
Evaporation rate:	Not Determined
Flammability (solid, gas):	Not Applicable
Upper/lower flammability or explosive limits:	Not Applicable
Vapor pressure:	Not Determined
Vapor density:	Not Determined
Relative density:	1.02 at 77°F (Water=1)
Solubility(ies):	Soluble
Partition coefficient: n-octanol/water:	Not Determined
Auto-ignition temperature:	Not Determined
Decomposition temperature:	Not Determined
Viscosity:	Not Determined

10.Stability and reactivity

- **10.1 Reactivity:** This material is considered to be non- reactive under normal use conditions.
- **10.2 Chemical stability:** Stable.
- 10.3 Possibility of hazardous reactions: Hazardous polymerization will not occur.
- 10.4 Conditions to avoid (e.g., static discharge, shock, or vibration): Not Applicable
- **10.5** Incompatible materials: Strong oxidizing agents.
- **10.6 Hazardous decomposition products:** Thermal decomposition is highly dependent on conditions. A complex

SAFETY DATA SHEET Super APC (VOC Compliant)

SDS No: 4015-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013) Date of last Revision: 08/19/2014

mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

11.Toxicological information

.

Description of the various toxicological (health) effects and the available data used to identify those effects, including:

11.1 Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):

- Inhalation: It may cause respiratory tract irritation. Do not breathe dust/fume/gas/mist/vapors/spray.
- **Ingestion:** May be harmful if ingested. Causes burns and gastrointestinal irritation with nausea, vomiting and diarrhea.
- Skin contact: Causes severe skin burns.
- Eye contact: Causes serious eye damage.
- 11.2 Symptoms related to the physical, chemical and toxicological characteristics: Not Determined
- **11.3 Delayed and immediate effects and also chronic effects from short- and long-term exposure:** See section 11.1.
- **11.4** Numerical measures of toxicity (such as acute toxicity estimates): Not determined on the mixture.

Name (Components)	Route	Species	Value
Sodium Metasilicate Pentahydrate CAS No:10213-79-3	Dermal	Rabbit	LD50>5000 mg/m3
66	Ingestion	Rat	LD50>1152 mg/kg
"	Inhalation (4 hours)	Rat	LD50>2060 ppm
Ethylene glycol monobutyl ether CAS No:111-76-2	Dermal	Rat	LD50 > 2000 mg/kg
"	Ingestion	Rat	LD50 > 1300 mg/kg
"	Inhalation-vapor (3 hours)	Rat	LC50 > 4.9 mg/l
Sodium Hydroxide CAS No:1310-73-2	Dermal	Rabbit	LD50 >1350 mg/m3
66	Ingestion	Rat	LD50 >300 mg/kg
"	Inhalation (4 hours)		No Data Available
Ethoxylated Alcohols Mixture	Dermal	Rabbit	LD50>5000 mg/m3
"	Ingestion	Rat	LD50>2000 mg/kg
"	Inhalation-aerosol (4 hours)	Rat	No Data Available

Skin Corrosion/Irritation

	Name (Components)	Species	Value	
--	-------------------	---------	-------	--

SAFETY DATA SHEET Super APC (VOC Compliant)

SDS No: 4015-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013) Date of last Revision: 08/19/2014

Sodium Metasilicate Pentahydrate CAS No:10213-79-3	Rabbit	Corrosive to skin.
Ethylene glycol monobutyl ether CAS No:111-76-2	Rabbit (24 hours)	Moderate irritation.
Sodium Hydroxide CAS No:1310-73-2	Human	Corrosive to skin.
Ethoxylated Alcohols Mixture		Moderate irritation

Serious Eye Damage/Irritation

Name (Components)	Species	Value
Sodium Metasilicate Pentahydrate CAS No:10213-79-3	Rabbit	Corrosive to eyes.
Ethylene glycol monobutyl ether CAS No:111-76-2	Rabbit (24 hours)	Moderate irritation.
Sodium Hydroxide CAS No:1310-73-2		Corrosive to eyes.
Ethoxylated Alcohols Mixture		Causes severe eye irritation. May cause severe corneal injury.

Respiratory or skin sensitization

Name (Components)	Species	Value
Sodium Metasilicate Pentahydrate CAS No:10213-79-3		Not a sensitizer
Ethylene glycol monobutyl ether CAS No:111-76-2	Guinea Pig	Not a skin sensitizer
Sodium Hydroxide CAS No:1310-73-2	Human	Not a sensitizer
Ethoxylated Alcohols Mixture	Human	No Data Available

Germ Cell Mutagenicity

Name (Components)	Route	Value
Sodium Metasilicate Pentahydrate	In Vivo	Negative
CAS No:10213-79-3		
Sodium Metasilicate Pentahydrate	In Vitro	Negative
CAS No:10213-79-3		
Ethylene glycol monobutyl ether	In Vitro: Salmonella typhimurium	Negative +/- activation
CAS No:111-76-2	assay (Ames test)	
Sodium Hydroxide	In Vitro: Salmonella typhimurium	Negative
CAS No:1310-73-2	assay (Ames test)	
Ethoxylated Alcohols Mixture	In Vitro	No Data Available

Carcinogenicity

Name (Components)	Route	Species	Value	
Sodium Metasilicate			Not classified	
Pentahydrate				
CAS No:10213-79-3				
Ethylene glycol			Not Classified.	
monobutyl ether CAS				

SAFETY DATA SHEET Super APC (VOC Compliant)

SDS No: 4015-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013) Date of last Revision: 08/19/2014

No:111-76-2		
Sodium Hydroxide CAS No:1310-73-2		Not Classified.
Ethoxylated Alcohols Mixture		Not Classified.

Reproductive toxicity

Name (Components)	Route	Species	Value	Test Result	Exposure Duration
Sodium Metasilicate Pentahydrate CAS No:10213-79-3			No relevant data found.		
Ethylene glycol monobutyl ether CAS No:111-76-2			Not Classified		
Sodium Hydroxide CAS No:1310-73-2			No relevant data found.		
Ethoxylated Alcohols Mixture			No relevant data found.		

Specific Target Organ Toxicity - single exposure

Name (components)	Route	Species	Target Organ	Value	Test Result	Exposure Duration
Sodium Metasilicate Pentahydrate CAS No:10213-79-3	Inhalation		Respiratory system	Causes irritation.		
Ethylene glycol monobutyl ether CAS No:111-76-2	Inhalation		Central Nervous System	May cause drowsiness or dizziness	NOAEL	
Sodium Hydroxide CAS No:1310-73-2				No relevant data found.		
Ethoxylated Alcohols Mixture				No relevant data found.		

Specific Target Organ Toxicity - repeated exposure

Name (components)	Route	Species	Target Organ	Value	Test Result	Exposure Duration
Sodium Metasilicate Pentahydrate CAS No:10213-79-3			organ	No relevant data found.		Datation
Ethylene glycol monobutyl ether CAS No:111-76-2	Dermal	Rat		150 mg/kg	NOAEL	
Sodium Hydroxide CAS No:1310-73-2				No relevant data found.		
Ethoxylated Alcohols Mixture				No relevant data found.		

SAFETY DATA SHEET Super APC (VOC Compliant)

SDS No: 4015-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013) Date of last Revision: 08/19/2014

Aspiration Hazard

Name (Components)	Value
Sodium Metasilicate Pentahydrate	Not Classified
CAS No:10213-79-3	
Ethylene glycol monobutyl ether CAS No:111-76-2	Aspiration Hazard Toxicity Category 1
Sodium Hydroxide	No relevant data found.
CAS No:1310-73-2	
Ethoxylated Alcohols Mixture	Aspiration Hazard Toxicity Category 1

12. Ecological information

- 12.1 Ecotoxicity (aquatic and terrestrial, where available): Not determined
- 12.2 Persistence and degradability: Not determined
- 12.3 Bioaccumulative potential: Not determined
- **12.4 Mobility in soil:** Not determined
- 12.5 Other adverse effects (such as hazardous to the ozone layer): Not determined

13.Disposal considerations

13.1 Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging: Dispose of contents/ container in accordance with the local/regional/national/international regulations. Do not contaminate any lakes, streams, ponds, or underground water supplies.

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death.

14.Transport information

Because this product is produced and shipped in several different container sizes, domestically and internationally, please consult your transportation specialist for the proper shipping name and class.

- **14.1 UN number:** Not Regulated
- 14.2 UN proper shipping name: Not Regulated
- 14.3 Transport hazard class(es): Not Regulated
- **14.4 Packing group, if applicable:** Not Regulated
- 14.5 Environmental hazards (e.g., Marine pollutant (Yes/No)): Not determined
- 14.6 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not determined

SAFETY DATA SHEET Super APC (VOC Compliant)

SDS No: 4015-1 Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013) Date of last Revision: 08/19/2014

14.7 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises: Not determined

15.Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question:

- OSHA Hazard Communication Standard: This material is classified as hazardous in accordance with OSHA 29 CFR 1910.1200 (see section 2).
- **TSCA:** Components of this product are listed on the TSCA Inventory.
- SARA Title III, Section 302 (Extremely Hazardous Substances): None
- SARA Title III, Section 313: This product contains 2-Butoxyethanol (CAS No: 111-76-2 ≤ 8.00%) which is subject to the reporting requirements of SARA Title III.
- SARA Title III, Section 311/312 Classifications:
 Fire Hazard: No
 Immediate Hazard: Yes
 Delayed Hazard: No

Reactivity Hazard: No

- CERCLA Hazardous Substances: This material contains Sodium Hydroxide (CAS No: 1310-73-2 ≤ 2.75% wt) which is subject to reporting (Reportable Quantity is1000 lbs) under the requirements of the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA). Contact local authorities to determine if other reporting requirements apply.
- Clean Air Act Section 112(r): None
- CLEAN WATER ACT/OIL POLLUTION ACT: None
- CA PROP 65:

WARNING! This product contains a chemical known to the State of California to cause cancer: None WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm: None

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16.Other information including date of preparation or last revision

Full text of H-Statements referred to under sections 2 and 3:

H227: Combustible liquid.

- H290: May be corrosive to metals.
- H304: May be fatal if swallowed and enters airways.
- H314: Causes severe skin burns and eye damage.
- H315: Causes skin irritation.
- H316: Causes mild skin irritation.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H335: May cause respiratory irritation.
- H336: May cause drowsiness or dizziness.
- Acute Tox.3 or 4: Acute Toxicity Category 3 or 4

SAFETY DATA SHEET Super APC (VOC Compliant)

SDS No: 4015-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013) Date of last Revision: 08/19/2014

Asp Tox.1 or 2: Aspiration Toxicity Category 1 or 2 Eye Dam./Irrit.1 or 2: Eye Damage/Irritation Category 1 or 2 Flam. Liq.2 or 3 or 4: Flammable Liquid Category 2 or 3 or 4 Skin Corr./Irrit.1 or 2 or 3: Skin Corrosion/Irritation Category 1 or 2 or 3 STOT SE3: Specific Target Organ Toxicity Single Exposure Category 3 Sources of key data used to compile the Safety Data Sheet: International Agency for Research on Cancer International Air Transport Association: Dangerous Goods Regulations. International Maritime Organization: International Maritime Dangerous Goods Code Components supplier data Globally harmonized system of classification and labeling of chemicals (GHS Rev.5th e.2013) **European Chemicals Agency website** EU Registration, Evaluation and Restriction of Chemicals regulation (REACH): Classification and Labeling Inventory US California Proposition 65 US Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) US Department of Health & Human Services. National Toxicology Program US Department of Transport DOT 49 CFR US National Fire Protection Association (NFPA) 704 US National Institute for Occupational Safety & Health (NIOSH) (exposure limits) US Occupational Safety & Health Administration (OSHA) 29 CFR 1910.1200 (Hazard Communication Standard) US OSHA 29 CFR 1910.1000 - Table Z1 (exposure limits) US Superfund Amendments and Reauthorization Act (SARA) Title III Sections 302: 311/312 : 313 US Toxic Substances Control Act (TSCA) Key or legend to abbreviations and acronyms used in the safety data sheet: ACGIH - American Conference of Governmental Industrial Hygienists CAS No - Chemical Abstract System No. CERCLA- US Comprehensive Environmental Response, Compensation, and Liability Act COC - Cleveland Open Cup (flash and fire point) DOT -Department Of Transportation **EPA - Environmental Protection Agency** IARC - International Agency for Research on Cancer IATA - International Air Transport Association IMDG - International Maritime Dangerous Goods code mg/m³ - milligrams per cubic meter mg/l - milligrams per liter NIOSH - National Institute for Occupational Safety and Health NFPA- US National Fire Protection Association NTP - National Toxicology Program OSHA - Occupational Safety and Health Administration **OEL-Occupational Exposure Limits** PEL - Permissible Exposure Limits ppb - Parts Per Billion ppm - Parts Per Million PMCC - Pensky-Martin Closed Cup (flash point) RCRA - EPA Resource Conservation and Recovery Act SARA - Superfund Amendments and Reauthorization Act Title I, II, III SDS - Safety Data Sheet STEL- Short Term Exposure Limit TCC - Tag Closed Cup (flash point)

SAFETY DATA SHEET Super APC (VOC Compliant)

SDS No: 4015-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013) Date of last Revision: 08/19/2014

TLV - Threshold Limit Value TWA - Time Weighted Average Exposure < - Less than > - More than Procedure used to derive the classification for mixtures according to Regulations 29 CFR 1900.1200 and GHS Rev.5th e.2013: Calculation method: Classification of mixtures based on ingredients of the mixture.

LEGAL DISCLAIMER:

The information contained in this document is based upon data believed to be reliable at the time of preparing this SDS and relates only to the matters specifically mentioned in this document.

Although J.B.Chemical Co. has used reasonable skill and care in the preparation of this information, in the absence of any overriding obligations arising under a specific contract, no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and J.B.Chemical Co. shall not be liable for any loss, damage or injury that may occur from the use of this information. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use of information contained in this document, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier of such information. J.B.Chemical Co. also dose not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

Prepared by: J.B.Chemical Regulatory Affairs

Revision Date: August 19, 2014

Preparation date: August 19, 2014