

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

676-003 **Product number**

Product name Carpet Spot Plus Effective date 11-Feb-2011 Sprayway, Inc. **Company information** 484 Vista Ave.

Addison, IL 60101 United States

General Assistance 630-543-7600 Company phone

800-424-9300 **Emergency telephone US Emergency telephone outside US** 703-527-3887

07 Version #

11-Feb-2011 Supersedes date

2. Hazards Identification

Emergency overview Aerosol. CONTENTS UNDER PRESSURE.

Harmful in contact with eyes. May be harmful if absorbed through skin.

Potential health effects

Routes of exposure Eye contact. Inhalation. Skin contact. Ingestion.

Eves Contact may irritate or burn eyes. Eye contact may result in corneal injury.

May be harmful if absorbed through skin. Frequent or prolonged contact may defat and Skin

dry the skin, leading to discomfort and dermatitis.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.

Ingestion Components of the product may be absorbed into the body by ingestion.

Target organs 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is

repeated and prolonged and may cause blood damage. These effects have not been

observed in humans.

Central nervous system. Lungs.

Unconsciousness. Conjunctiva. Cyanosis (blue tissue condition, nails, lips, and/or skin). **Chronic effects**

May be harmful if absorbed through skin. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the

skin, leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Corneal damage. Narcosis. Cyanosis (blue tissue condition,

nails, lips, and/or skin). Coughing. Conjunctivitis. Defatting of the skin. Skin irritation.

3. Composition / Information on Ingredients

Components	CAS#	Percent
Diethylene Glycol Monobutyl Ether	112-34-5	8 - 10
2-Butoxyethanol	111-76-2	8 - 10
n-Butane	106-97-8	3 - 5
Propane	74-98-6	1 - 3
Non-hazardous and other components below reportable levels		

4. First Aid Measures

First aid procedures

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact Eye contact

lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Immediately flush skin with plenty of water. Remove and isolate contaminated clothing Skin contact

and shoes. Get medical attention immediately. Wash clothing separately before reuse.

Product name: Carpet Spotter Plus

MSDS US Product #: 676 Carpet Spot Plus

1/5

Inhalation Ingestion

Move to fresh air. Call a physician if symptoms develop or persist.

In the unlikely event of swallowing contact a physician or poison control center. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If ingestion of a large amount does occur, call a poison control center immediately.

5. Fire Fighting Measures

Flammable properties

Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media

Protection of firefighters

Alcohol foam. Dry chemical. Carbon dioxide (CO2).

Protective equipment and precautions for firefighters In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures

Methods for containment

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.

Methods for cleaning up

Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure.

Storage

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and flame. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Avoid exposure to long periods of sunlight. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 1 Aerosol (NFPA 30B)

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

1440.04.5			
yi 112-34-5	20 ppm	Not established	Not established
111-76-2	20 ppm	Not established	Not established
106-97-8	1000 ppm	Not established	Not established
74-98-6	1000 ppm	Not established	Not established
	106-97-8	111-76-2 20 ppm 106-97-8 1000 ppm	111-76-2 20 ppm Not established 106-97-8 1000 ppm Not established

OSHA

Components	CAS#	TWA	STEL	Ceiling
Diethylene Glycol Monobuty Ether	yl 112-34-5	100 ppm	Not established	Not established
2-Butoxyethanol	111-76-2	50 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection Skin protection

Not normally needed. Chemical goggles are recommended. Do not get in eyes.

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Product name: Carpet Spotter Plus

MSDS US 2/5 Product #: 676 Carpet Spot Plus

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance Compressed liquefied gas. **Boiling point** 230 °F (110 °C) estimated

Color Colorless.

Density 0.9421 g/cm3 estimated **Flammability (HOC)** 8.06 kJ/g estimated

Flash back No.

Flash point -156 °F (-104.4 °C) estimated

Form Aerosol.
Freezing point Not available

OdorButylpH11.5 - 12.5Physical stateLiquid.

Pressure 50 - 60 psig @70F
Solubility Completely
Specific gravity 0.9422 estimated

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition. Instability caused by elevated temperatures.

Conditions to avoid Heat, flames and sparks.

Hazardous decomposition products Irritants.

11. Toxicological Information

Acute effects Acute LD50: 2322 mg/kg estimated, Rat, Dermal

Acute LC50: 23 mg/l/4h estimated, Rat, Inhalation

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

2-Butoxyethanol 111-76-2 Inhalation LC50 Rat 2.21 mg/L 4 h; Inhalation LC50 Rat 450 ppm 4 h; Oral LD50 Rat

470 mg/kg; Dermal LD50 Rat 2270 mg/kg; Dermal LD50 Rabbit 220 mg/kg

Diethylene Glycol Monobutyl Ether 112-34-5 Oral LD50 Rat 3384 mg/kg; Dermal LD50 Rabbit 2700 mg/kg

 n-Butane
 106-97-8
 Inhalation LC50 Rat 658 mg/L 4 h

 Propane
 74-98-6
 Inhalation LC50 Rat 658 mg/L 4 h

12. Ecological Information

Ecotoxicity LC50 7225 mg/L, Fish, 96.00 Hours,

EC50 12002 mg/L, Daphnia, 48.00 Hours,

Contains a substance which causes risk of hazardous effects to the environment.

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]

Disposal instructionsContents under pressure. Dispose of this material and its container to hazardous or

special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306
Packaging non bulk 156, 306
Packaging bulk None

IMDG

Basic shipping requirements:

Proper shipping name AEROSOLS

Hazard class2.1UN number1950

Additional information:

Packaging exceptionsLTD QTYItem5FLabels requiredNoneTransport Category2



Basic shipping requirements:

Proper shipping name Aerosols, flammable

Hazard class2.1UN number1950

Additional information:

Packaging exceptions LTD QTY
Labels required 2.1





15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

2-Butoxyethanol 111-76-2 1.0 % de minimis concentration (applies to R-(OCH2CH2)n-OR', where n = 1,2, or 3,

R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or

sulfonate, Chemical Category N230)

Diethylene Glycol Monobutyl Ether 112-34-5 1.0 % de minimis concentration (applies to R-(OCH2CH2)n-OR', where n = 1,2, or 3,

R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or

sulfonate, Chemical Category N230)

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous Yes

chemical

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely No

hazardous substance

Section 311 hazardous chemical Yes

Hazard categories (311/312) Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

2-Butoxyethanol 111-76-2 Present

Diethylene Glycol Monobutyl Ether 112-34-5 Environmental hazard

 n-Butane
 106-97-8
 Present

 Propane
 74-98-6
 Present

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 1

Flammability: 2 Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and

experience currently available.

MSDS sections updated Product and Company Identification: Product and Company Identification

Prepared by Regulatory Compliance